



A high quality, water based lacquer which distends to a perfect smoothness. Can be used on any interior or exterior surfaces.

Kyoto H²O exists en Mat, Velvet, Eggshell or High Gloss

USAGE

Interior and exterior masonry and woodwork






PREPARATION

(Ensure surfaces are sound, clean, dry and free from grease.
For all absorbant surfaces (plaster, wood, etc...) apply 1 coat of "Fond de Teint" premium primer.
For any other surface (tiles, plastic etc...) apply "Restart" multi surface primer.

TECHNIQUE

Apply two coats of Kyoto H²O using a medium bristled roller or brush.
When applying deep shaded colours make sure that you have prepared the substrate using the adequately tinted "Fond de teint"

DILUTION, DRYING AND COVERAGE

 <p>up to 10% water</p>	 <p>up to 10% water</p>	 <p>Touch dry : 30mn</p> <p>Recoat: 4 hrs</p>	 <p>8 - 12 m² per liter</p>	 <p>Clean Up : Use warm water and soap to clean tools.</p>
--	--	--	---	---

PROTECTION

Kyoto H²O, once dry, has a very high level of mchanical resistance and does not need to be protected.

COLOURS & PACK SIZE

147 colours - Inspirations + 1050 colours - Colour Box + bespoke colours
750ml / 2,5 L / 4L / 14 L (mat only)

FORMULATION AND TECHNICAL DETAILS

Density :1,060 à 1,260 g/ltr
Modified acrylic resins, titanium dioxide and selected fillers
Solids by weight : 40%
Flash point : In-inflammable
Thickness : 40 µm
VOC - maximum value : < 75gr/ltr - Low
(Fiche technique version 2011/01)